

Metric Rod Ends

Inquiry Template



Fax to:

704-588-5738

P.T. International Corp.

Attn: _____

From: _____

Company: _____

Phone: _____

Comments: _____

Center Distance = _____ mm

Thickness t= _____ mm (observe Spherical width!)

Material: _____ with 2x Sphericals: _____

Please indicate: _____ Form A _____ Form B

Center Distance = _____ mm Adjustable Range = +/- _____ mm

Ridge to identify left hand thread

Left hand thread

Hexagon SW= _____ alternative: Pipe Ø _____ with cross bore

Length= _____ mm Material: _____

Lock Nut DIN 439 (flat) Material: _____

Rod End

Center Distance = _____ mm Adjustable Range = +/- _____ mm

Left hand thread

Threaded Rod Length= _____ mm Material: _____

Lock Nut DIN 439 (flat) Material: _____

Rod End

with incorporated Spherical Type: _____

Head Width M= _____ mm, Ball Width B= _____ mm

Thread Length GL= _____ mm, Thread G= _____

Material Ball: _____

Material Outer Ring: _____

Maintenance free: Yes No

Nomenclature:

Female Thread: The letter **I** is the second letter in the product reference e.g. GI or EI

Male Thread: The letter **A** is the second letter in the product reference e.g. GA or EA

Left Hand Thread: The letter **L** is the third place in the product reference e.g. GAL or EAL

Non-Standard Thread: Bearing reference with additional thread specification e.g. GISW 30, **M 27x2**

Stainless Steel Ball: The letter **R** will be added after size reference e.g. GIRSW 10 **R**, GXSW 10 **R**, stainless version

Completely Stainless: The letters **SS** will be added after size reference e.g. GE 10 EC-**SS** or EI 16 D-**SS**

Ball Hard Chrome Plated: **ICR** will be added after size reference e.g. GASW 10 **ICR**

Seals: -**2RS** will be added after size reference e.g. GISW 10-**2RS**

Threaded Bolt: **Bo** will be added after size reference e.g. GISW 10 **Bo**

Nickel Plated Housing: **NI** will be added after size reference e.g. GISW 14 **NI** (improved corrosion resistance for the housing)

Left Hand Thread for Hydraulic Rod Ends: The letter **L** will be added at the third place replacing the letter R e.g. **FPL...N**